



Clamping Head

High-rigidity and high-precision spring collet.

Quick installation and removal within 10 seconds using a dedicated tool.


Wide clamping range, compatible with robotic arms.a



S-Smooth



R-Radial Grooves



RL-Radial and Longitudinal Grooves

EM-Emergency

1

Type	Ref.	L	D	d ●	d ■	d ◆
32	32S	44	57.7	6-32	7-27	7-22
	32R	44	57.7	8-32	8-27	8-22
	32RL	44	57.7	11-32		
	32EM	44	57.7	4-32		

Type	Ref.	L	D	d ●	d ■	d ◆
42	42S	42	79.3	6-42	7-38	7-30
	42R	42	79.3	8-42	8-38	8-30
	42RL	42	79.3	11-42		
	42EM	42	79.3	4-42		

Type	Ref.	L	D	d ●	d ■	d ◆
52	52S	46	79.3	6-52	7-45	7-36
	52R	46	79.3	8-52	8-45	8-36
	52RL	46	79.3	11-52		
	52EM	46	79.3	4-52		

Type	Ref.	L	D	d ●	d ■	d ◆
65	65S	53	99.5	6-65	7-56	7-46
	65R	53	99.5	8-65	8-56	8-46
	65RL	53	99.5	11-65		
	65EM	53	99.5	4-65		

Type	Ref.	L	D	d ●	d ■	d ◆
80	80S	53	114.5	6-80	7-68	7-56
	80R	53	114.5	8-80	8-68	8-46
	80RL	53	114.5	11-80		
	80EM	53	114.5	4-80		

Type	Ref.	L	D	d ●	d ■	d ◆
100	100S	59	144.5	40-100		
	100R	59	144.5	40-100		
	100RL	59	144.5	40-100		
	100EM	59	144.5	40-100		

For more models, please contact us to request information.