



Clamping Head For Multi-Spindle



S-Smooth

Type	Ref.	L	D	●	A	by
Index MS16	16I	35	44.3	4-16	L	0.5
				8-16	R	0.5
				11-16	RL	0.5

R-Radial Grooves

RL-Radial and Longitudinal Grooves

Type	Ref.	L	D	●	A	by
Index MS18	22I	36	44.3	4-22	L	0.5
				8-22	R	0.5
				11-22	RL	0.5

EM-Emergency

Type	Ref.	L	Ref.	L	D	●	A	by
Index MS22	9022L	37	9022BL	40	44.3	4-22	L	0.5
	9022R	37	9022BR	40	44.3	8-22	R	0.5
	9022RL	37	9022BS	40	44.3	11-22	RL	0.5

Type	Ref.	L	D	●	A	by
Index MS32	32I	47.15	61	4-32	L	0.5
				8-32	R	0.5
				11-32	RL	0.5

Type	Ref.	L	D	●	A	by
Schutte AF26, SE25, SE26, SF26-S	39S	38	60.5	4-26	L	0.5
				8-26	R	0.5
				11-26	RL	0.5

Type	Ref.	L	D	●	A	by
Mori Say 6-26	69B	43	69.8	6-32	L	0.5

Type	Ref.	L	D	●	A	by
index ABC	42I	43	69.8	6-32	L	0.5